



**AIA STANDARDS MEMORANDUM**

February 29, 2024

TO: National Aerospace Standards Committee (A6)

FROM: Nathan Phillips, Director, Standards  
 SUBJ: NAS/NASM Mailing 24-02

NAS No.	Date	Rev	Status	Project/Custodian	3D	Title
NA0007	February 29, 2024	3	R,S	P755AIA-22101S	N	METRIC FASTENERS, TITANIUM ALLOY, EXTERNALLY THREADED, 1100 MPa TENSILE, 660 MPa SHEAR
NA0271	February 29, 2024	2	S	P755AIA-24101S	N	PROCUREMENT SPECIFICATION, METRIC FASTENERS, CRES 300 SERIES, EXTERNALLY THREADED, MJ THREAD, 500 MPa Ft <sub>u</sub> and 700 MPa Ft <sub>u</sub>
NAS186	February 29, 2024	3	S	P755AIA-22239S	Y	SPACER, STEPPED, SWAGE TYPE
NAS287	February 29, 2024	6	R,S	P755AIA-24103S	N	TERMINAL, CHAIN TO CABLE (FOR SWAGING)
NAS387	February 29, 2024	4	**	P2337AIA	Y	SCREW, 100° OVAL CROSS RECESSED HEAD, MACHINE (COARSE & FINE THREAD)
NAS399	February 29, 2024	3	S	P755AIA-24104S	N	LATCH, PUSH BUTTON, ADJUSTABLE
NAS576	February 29, 2024	5	**	P755AIA-23439	N	THREAD LENGTH FOR SELF-LOCKING NUTS
NAS1029	February 29, 2024	6	R,S	P755AIA-24105S	Y	NUT, SELF-LOCKING, PLATE, TWO LUG, REGULAR HEIGHT, BEVEL SEAT
NAS1072	February 29, 2024	3	R,S	P755AIA-22104S	N	GUARD, CHANNEL, TOGGLE SWITCH
NAS1327	February 29, 2024	1	R,S	P755AIA-22108S	N	SPACER, THRU-HOLE, SPLINE
NAS1554	February 29, 2024	5	R,S	P755AIA-24106S	Y	GROMMET, PTFE, SPLIT
NAS1575	February 29, 2024	3	**	P755AIA-24136	N	COVER, SWITCH FITTING BOX, WEATHERPROOF
NAS1776	February 29, 2024	3	R,S	P755AIA-22119S	Y	NUT, SELF-LOCKING, PLATE, ONE LUG, LOW HEIGHT, CBORED, REDUCED RIVET SPACING, 160 KSI, 450 °F, 800 °F
NAS1791	February 29, 2024	5	**	P2011BF	Y	NUT, SELF-LOCKING, PLATE, TWO LUG, FLOATING, VARIABLE COUNTERBORE, REPLACEABLE NUT ELEMENT, 125 KSI FT <sub>u</sub> , 450 °F AND 800 °F

NAS1792	February 29, 2024	4	**	P2012BF	Y	NUT, SELF-LOCKING, PLATE, ONE LUG, FLOATING, VARIABLE COUNTERBORE, REPLACEABLE NUT ELEMENT, 125 KSI FTU, 450 °F AND 800 °F
NAS1793	February 29, 2024	5	**	P2013BF	Y	NUT, SELF-LOCKING, PLATE, CORNER, FLOATING, VARIABLE COUNTERBORE, REPLACEABLE NUT ELEMENT, 125 KSI FtU, 450 °F AND 800 °F
NAS1835	February 29, 2024	10	**	P755AIA-24140	Y	INSERT, MOLDED IN, BLIND THREADED, LOCKING, NONLOCKING, FLOATING, SANDWICH PANEL
NASM17731	February 29, 2024	2	**	P2321AIA	Y	FASTENER, ROTARY, QUICK-OPERATING, FLUSH HEAD, FLOATING TYPE, 2,210 LBF MIN TENSILE STRENGTH
NASM35333	February 29, 2024	5	**	P2313AIA	Y	WASHER, LOCK, FLAT, INTERNAL TOOTH
NASM43770/11	February 29, 2024	3	**	P755AIA-23449	N	SNAP HOOKS, CAST BODY, FIXED LOOP EYE W/O ROLLER, FLAT SPRING CLOSURE, LIGHT DUTY
NASM45595/9	February 29, 2024	2	R,S	P755AIA-24110S	Y	WASHER, SHOULDERED, GLASS FILLED NYLON

Status Legend:

**	New Revision	*	Inactive for New Design
+	New Standard	X	Cancelled
R	Reaffirmed	RA	Reactivated
S	Stabilized	A	Amendment

Enclosures

cc: NASC A1, A2, A3 (without enclosures)